



54"/ TYPE II / 20 oz. **LOW VOC** **RECYCLED CONTENT**

### PHYSICAL PROPERTIES

---

**Weight** 20 oz. PLY/620 G/PLM 13.3 oz. PSY/451 G/PSM  
**Width** 54"/137 cm  
**Backing** Osnaburg  
**Match** Straight, random

Custom colors, weights, and micro venting available

Meets or exceeds Federal Specification CCC-W-408D

### FIRE SAFETY

---

- Class "A" Fire rated - Tested in accordance with ASTM E-84 Tunnel Test
- Passes Class "A" NFPA 101 Life Safety Code
- Passes NFPA 286 Corner Burn Test
- Tested in accordance with CAN/ULC S102.2

See website or contact us for additional results

### ENVIRONMENT & HEALTH

---

- **Contains 10% recycled content**
- **Certified to NSF/ANSI 342 Sustainability Assessment; ask distributor for details**
- **Meets California section 01350 IAQ test requirements for wallcovering**
- **Complies with USGBC LEED v4 Criteria, under Indoor Environmental Quality (CDPH/EHLB/Standard Method Version 1.1, 2010)**

### ANTIMICROBIAL FEATURES

---

Bolta®wallcoverings contain antimicrobial additives to resist the growth of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls. All Bolta®wallcoverings can be perforated, with a 30 yard minimum requirement, for enhanced permeability. This product is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation and/or accumulation at wall cavities and wall surfaces, particularly in warm, humid climates.

### WARRANTY

---

5 year warranty against manufacturing defects. Additional information is available at [www.boltawallcovering.com](http://www.boltawallcovering.com)